

i-MO Mini Series 5G Router

OptiBond™



Advanced Bandwidth Technologies

Network Resilience ~ connectivity wherever & whenever you need it...

The i-MO Mini series 5G router is ideal for providing a small branch office, home office, temporary location or mobile service with a highly resilient, high speed connection to the Internet.

With an internal 5G compatible modem and a WAN Port available, the appliance can be configured for failover, load-balancing or bonding to increase reliability and available bandwidth. Application data can be routed over 5G, WAN or load balanced.

As businesses move to Cloud based applications the reliability and speed of Internet connectivity is business-critical. i-MO enables companies to seamlessly add extra capacity whilst reducing WAN total cost of ownership.

The i-MO Mini with our unique OptiBond software is ideally suited to mobile and Internet of Things type applications.

The Administrative Web/CLI Interface easily allows the appliance to be configured for link-failover (e.g. from WAN to cellular).

The appliance is powered from a single 12V power supply. This can either be provided by the included external AC adapter (100–240V, 50-60Hz) or alternatively it can be powered from a standard 12V DC supply.

The i-MO Mini is supplied with a pre-drilled, steel base plate to allow for secure mounting in almost any environment.

Software Features

i-MO Mini Series	
i-MO Firmware with	Bandwidth Aggregation Intelligent Failover Session Persistence
WAN	Static IP WAN Link Health Check
LAN	Multiple LAN subnets supported DHCP Server DHCP Reservation
VPN	IPSec Site-to-Site mode Ciphers: AES and 3DES Hashes: MD5 and SHA1 Pre-shared Key NAT-Traversal
Firewall	Stateful firewall Multiple zones: WAN, DMZ, LAN Multi NAT IP Forwarding Port Forwarding
Device Management	Web Administrative Interface Export / Import Configuration Command Line Interface



i-MO Mini Series Bonding Router



Technical Specifications	Mini
Format	Mobile / Desktop
Dimensions (WxHxD)	104 x 30 x 113 mm
Status	Power LED + 5G Status
USB	2 x USB 3.0
Cellular Data Connectivity	1 x 5G Modem
Antenna Connectors	2 x SMA
LAN / WAN Interface	2 x Gigabit Ethernet (Max 1 x WAN)
Power Input	USB-C 12VDC +/- 5% @ 2.5A
Power Supply	External AC Adapter 110 - 220 VAC (47 - 63Hz)
Max Power Consumption	Estimated power consumption : 25W (Wifi + 4G)
Operating Temperature	0°C to +50°C
Storage	Room Temperature
Humidity	10% to 90% (non-condensing)
CPU	Broadcom 4-Core Cortex A72 @ 1.6Ghz
Max Bonded Throughput	> 150 Mbps
Memory	Up to 8 Gb
Storage	Up to 32 Gb

Features

Software

i-MO Firmware with:
OptiBond Advanced Bandwidth
Technology
Intelligent Failover
Session Persistence

Device Management

Web Administrative Interface
Export / Import Configuration
Command Line Interface

WAN

Static IP
WAN Link Health Check

LAN

Multiple LAN subnets supported
DHCP Server
DHCP Reservation
DNS Server

WLAN


No—External Access Point
recommended

VPN

IPsec VPN
Site-to-Site mode
Ciphers: AES and 3DES
Hashes: MD5 and SHA1
Pre-shared Key
NAT-Traversal

Firewall

Stateful firewall with support for PPTP,
FTP,SIP,H.323
Multiple zones: WAN, DMZ, LAN
Multi NAT
IP Forwarding
Port Forwarding



UK Head Office:
Electronic Media Services Ltd
1st Floor, Building 51,
Whitehill & Bordon Enterprise Park,
Budds Lane, Bordon, Hampshire, GU35 0FJ
Tel: +44 (0)1428 751655
Fax: +44 (0)1428 751654
e-mail: imo@ems-uk.com

